

iPECS

Your Communications Solution

The content of this document is subject to revision without notice due to continued progress in methodology, design and manufacturing. Ericsson-LG Enterprise shall have no liability for any error or damage of any kind resulting from the use of this document

© Ericsson-LG Enterprise Co., Ltd. 2023 Version 1.0

Ericsson-LG Enterprise Co., Ltd.
(08503) 189, Gasan digital 1-ro, Geumcheon-gu,
Seoul, South Korea
Telephone: +82-2-3777-1114
Fax: +82-2-480-7240
www.ericssonlg-enterprise.com
www.iPECS.com

iPECS is an Ericsson-LG Brand



Design Your Business Communications with iPECS UCP





As your workforce becomes more mobile and dependent on ease of collaborations, your communications solution should be simple, flexible and cost effective. For a business to perform and stay competitive, regardless of size, it needs tools that work well together to facilitate fast, well informed, critical decision making in a more efficient work environment.



PRODUCTIVITY ENHANCEMENT OF YOUR BUSINESS WITH UNIFIED COMMUNICATIONS SOLUTION

In business, you need to constantly improve and maximize productivity. Here is a solution, iPECS UCP and iPECS UCS. iPECS UCP is the core platform, and iPECS UCS is an application that provides unified communications solution through integration with iPECS UCP. iPECS UCS delivers a wide range of benefits to the SME customer as a built-in simple UC application. It can also be seamlessly expanded for a feature rich full UC solution for the enterprise customers. In addition, iPECS UCP provides various applications and communication tools, so users can easily work and communicate more effectively with their customers and coworkers more effectively than ever before.

iPECS UCS client is an intuitive desktop and mobile application designed for ease of use. And wherever you are, you can reach the resources needed for efficient communications. With a simple click, iPECS UCS client instantly accesses shared resources such as a central company directory and schedule synchronization. With presence information, users can reduce communication latency and communicate with others in the most appropriate format, Instant Message, voice call, video conference, SMS and more. To help improve decision making and response time, Users can use applications sharing, files sharing and other features that are provided to review the latest information such as sales records. iPECS UCS will simplify your business communications and will improve productivity by linking voice and other communications under an intuitive user interface.

LOWER TCO AND COMMUNICATION EXPENSES

Ericsson-LG Enterprise has been focused on all size businesses for more than 50 years and this experience is reflected in our products and solutions. The best of which is the iPECS UCP, from SME to Enterprise, to help you save money and lower costs. iPECS UCP employs two types of deployment which are a fully distributed modular architecture and virtualization scenario to deliver all the advantages of VoIP. These two voice and data infrastructures significantly reduce the costs of managing your business communications solution.

iPECS UCP is designed as a uniquely all modular IP system with distributed architecture. It's possible to provide an economical communications environment such as managing multi-sites or mobile offices. The modular type gateways, terminals and soft clients can be located anywhere there is access to your network. As users can connect anywhere, call charges decrease and business productivity increases. In addition, iPECS UCP is easily scalable with licenses. This scalability saves up-front investment costs and also protects future investment.

Furthermore, iPECS UCP provides virtualization solution which offers all the functionality and features of UC solutions as well. It can be deployed alongside other virtual applications in your VMware, AWS or MS Azure enabled data centers and it delivers a simple way to manage and enhance UC applications cost-effectively.

EASY TO USE AND MANAGE

Whether you're adding a new employee, moving phones, dispatching a road warrior or deploying a new branch office, iPECS UCP always makes it simple to do.

With a simple and straight-forward configuration along with plug and play installation, IT managers appreciate the ability to locate where iPECS solutions are needed without clumsy and difficult configuration limits. Users can also manage personal settings like voicemails, presence settings and call recordings. The user interface is intuitive and consistent across devices, making deployment and training a breeze.

Thanks to the modular and virtualized structures, you can simply add a license to increase the capacity or coverage of service as a business grows.

Simple and Cost Effective Way to Use UC&C and Mobility Solutions

Unified Communications Platform, iPECS UCP

iPECS UCP is Ericsson-LG Enterprise's Unified Communications Platform designed to meet SME and Enterprise communications needs. As ground breaking innovative platform, iPECS UCP provides out of box UC and Mobility solution. In addition, iPECS UCP is scalable for premium UC solution.



Embedded UC and Telephony

As the most compelling advantage, UC features are embedded in iPECS UCP. Users can improve business efficiency and productivity with embedded UC features including real-time voice, video and presence enabled IM with messaging services (Visual Voice Mail and SMS etc.) under a single user interface on multiple devices.

Rich Business Applications

iPECS UCP provides a various range of applications and mobile clients to fulfill varying needs and requirements in the SME environments. Also, it offers interoperability with various 3rd party solutions in hospitality, healthcare and other vertical industries.

Wide Range of Mobility

iPECS UCP provides multiple mobility solutions to improve business productivity and decrease communication expenses. Various options of iPECS IP DECT provides feature rich and reliable communications for high demanding mobile workers. iPECS UCS mobile client delivers the power of a desk phones to smartphones or tablet PCs for external mobile workers.

Ultimate Flexibility on Deployment

iPECS UCP as "Modular ALL-IP Architecture" enables flexible and cost-effective multi-site deployment with industry-unique architecture. Furthermore, virtualized deployment is supported to maximize flexibility on deployment as well. (iPECS vUCP is needed) It can be fully networked in T-NET (Transparent Networking) or Networking mode with local survivability and PSTN failover. Also, it provides call server (Local/Geo) and power redundancy for seamless communications environment. Through flexible T-NET and redundancy features, IT managers can easily manage a multi-site architecture. Leverage your business to full of flexibility with wide range of deployment scenarios.

Seamless Scalability

As a scalable call server iPECS UCP allows businesses to easily expand capacity with optional gateways or boards. In addition, simple system port licensing enables upfront investment savings and cost-effective expansion as a business grows. Not only system capacity, communications features including UC solution also can be expanded or added with simple license.

Simple Deployment and Management

iPECS UCP with its unique architecture fits for various business environments in a simple and cost-effective way. An Installation wizard simplifies the initial installations. In addition, intuitive and customizable Web-admin enables simple management for IT managers. Also, there is another type of web portal for end-user which is called 'Web User Portal'. End-users can easily set up basic personal settings anywhere via desktop or even on a mobile.

Virtualize Your Business Communications

iPECS vUCP, as a software base call server is running on VMware, AWS or MS Azure virtual environment. The software is same as on-premise iPECS UCP and all the system features as well. Under the equal user experiences, iPECS vUCP will make easy deployment for your business communication's flexibility and scalability. Also, it delivers an innovative way to manage diverse business applications and collaborate cost-effectively, so you can leverage business communications while keeping all the advantages of iPECS UCP. Get your 90-day trial license of iPECS vUCP that will allow you to try out all of the features.

Seamless Scalability by License

Users can easily expand capacity of their system starting with a base of each models with simple license.



" Seamless scalability by license "

Competitive Feature Set

Built-in system feature set and UC server provide various business applications and collaboration features to meet a variety of customers' needs.

Modular All-IP Architecture

As modular all-IP architecture, iPECS UCP enables flexible and cost-effective multi-site deployment with industry-unique architecture. Up to 100 call servers of T-NET (Transparent networking) are supported with local and geographical survivability and PSTN failover. Intelligent gateway modules can be deployed at any location. And high reliability with server redundancy and power redundancy is provided for seamless communication.

Emergency/Alarm Call Service

iPECS UCP provides wide range of emergency/alarm call services (Emergency call, emergency paging upto 50 groups, recording, monitoring, SOS paging, pre-recorded announcement, automatic triggering etc.) by the system itself. With embedded alarm call services, users can take an action rapidly for various emergency situations. For effective management, an automatic call with announcement can play and trigger an external relay contact. Also, all emergency calls are monitored and recorded in the emergency mailbox.

One Number Service

iPECS UCP provides one number service to users anywhere on any device. Users can have a consistent experience over multiple devices with seamless call control between devices. For example, when a user's master station receives a call, all devices will receive the call simultaneously. With one number service, users can experience a maximized business communication continuity.

Embedded VoIP

Embedded VoIP channels are one of the great advantages with iPECS UCP. In addition, iPECS UCP100/600 provides embedded VoIP relay (VoIP Switching) to provide more cost-effective VoIP channels (Max 16/24 channel by license). iPECS UCP's VoIP switching supports out-band SIP, T-NET and remote device/clients. Also, it provides Call Progress Tone Generation such as Ring Back tone, Busy/Error tone, Confirmation tone, etc. A completed feature-set of VoIP Switching can offer big cost benefits for overall business communications.

Integration with 3rd Party Solution

iPECS UCP provides easy integration with diverse 3rd party solutions. iPECS UCP provides a cost-effective way to use the existing solution with high compatibility by applying universal interfaces such as Web API. Generally, direct or middleware integration is supported. When user has a local solution such as hospitality and healthcare solutions, it can be easily integrated and offer more convenient iPECS features than before through various middleware support. Also, interworking with MS Teams is possible through Call2Teams middleware.

Embedded Voice Mail

iPECS UCP delivers sophisticated and easy to use voice mail services by default and can seamlessly be expanded as required. With the embedded voice mail channels (8 channels by default) and many valuable voice mail features to enhance the customers interactions, (Multiple user greetings, E-mail notification, VM cascading, Centralized or Distributed voice mail services for multi-location businesses and Multi language service etc.) These features are designed to increase the user's productivity with great Cost Advantages.

Multi-Tier Mobility and Mobile Extension

iPECS UCP is maximized for mobility solutions. Users can design multiple mobility solutions for both in and out of the office with either TDM and IP environment. In the office, IP DECT is available with essential features like system directory search and dial, alarm/emergency text messaging with 3rd party solutions. Max 254 IP DECT bases with 1000 handsets can be registered with seamless in-call handover as well as enhanced failover support to redundant call server. For out of the office, iPECS UCS mobile client covers rich communications features for mobile workers. In addition, Mobile extension feature is provided for seamless communications and ease of use. Through Mobile extension, calls can be seamlessly and easily moved back and forth between desk phone and mobile phone.

Easy Audio Conference

iPECS UCP provides a built-in audio conference bridge for cost-effective collaboration that can be easily expanded as required. With embedded conference features, users can collaborate easier than ever. There are 3 types of audio conference features. Conference Groups, pre-created conference members can easily initiate a group call to all members. Conference Rooms, pre-assigned conference rooms members can join the conference room with a password at any time with any device. And lastly, Ad-hoc Conference as multi-party conference can be easily set-up by the initiator. Conference capacity maximum is 200 rooms and 160 groups, each up to 32 parties.

Simplified Multiple Calls Handling

iPECS UCP provides for multiple call handling to allow seamless communications. A desktop phone's DSS buttons can be assigned for handling multiple calls. (Max 48 buttons) With preassigned buttons, users can easily handle multiple calls. For example, when a user is busy on a call and another call is presented to the station, the user can easily decide to answer or transfer the new call based on the pop up CID information using one of the preassigned buttons. When a user decides to answer the new call, the first call is placed on hold automatically allowing for easy and seamless communications.

Simple Deployment and Management

iPECS UCP is well organized with multiple levels of user-friendly administration tools. With an enhanced Installation wizard and Web-admin, IT managers can deploy and manage the system with ease. With intuitive and customizable Web-Admin, users can program and maintain the system via local or remote connection. Snap shot information of system resource usage like CPU, memory and storage enables a quick access to important system performance indicators. System alarm events and in-advance alerts can be notified to pre-assigned emails and call extensions so that the system can be managed in an appropriate way. (Alarm from external alarm relay contacts, Geo-redundancy failover notification, Emergency call notification, Bath alarm, Fault information, Capacity full and License expiration etc.) Also, there is a 'Web User Portal' for end-users to deliver fast customization by themselves. End-users can easily set up basic personal settings (Call Forward, Mobile Extension, Message, Voice Mail, Station Name etc.) anywhere via desktop or from their smart phone or tablet.

iPECS UCS Introduction


iPECS UCP provides powerful UC and collaboration features with built-in or external type of UCS server and clients.

iPECS UCS Highlight

UCS Standard (Built-in) <ul style="list-style-type: none"> No additional H/W server and installation 	Rich Presence & IM Continuity <ul style="list-style-type: none"> Integrated presence and personal status IM continuity among devices 	High quality Video Conference <ul style="list-style-type: none"> Max nine party video conference, sharing for document, desktop and application 	MS Outlook Integration <ul style="list-style-type: none"> MS Outlook calendar integration and click to call from MS Outlook 	Multi Log-in Support <ul style="list-style-type: none"> Support multi log-in for multiple devices at the same time with single ID/PW
--	---	---	---	--

※ iPECS UCS features are dependent upon server types (Standard/Premium) and user base license (Basic/Advanced/Power).
For more details, refer to below table.

iPECS UCS server types



iPECS UCS Feature Set by Server Type and User License


Server Type	Features	Basic User License	Advanced User License	Power User License
UCS Standard	Usable UCS client	Desktop (Call Control only)	Desktop/Mobile/Tablet	Desktop/Mobile/Tablet
	Log-in management	Single	Single	Multi
	One UCS account	0	0	0
	Desktop Call Control mode	0	0	0
	Mobile MEX mode	-	0 (Mobile / Tablet)	0 (Mobile / Tablet)
	Call log / Call log sync	0 / 0 (Desk phone & UCS Call Control)	0 / 0	0 / 0
	IM (1:1)	0	0	0
	Click to call	0	0	0
	Voice call	-	0	0
	iOS callkit (iOS only)	-	0 (Mobile iOS)	0 (Mobile iOS)
	Video call (1:1)	-	0	0
	On-demand recording (Desktop / Mobile)	0 / 0	0 / 0	0 / 0
	Flexible button (Desktop)	0	0	0
	Visual Voice Mail	0	0	0
	Audio conference manager	0	0	0
CRM integration	0	0	0	
MS Outlook sync (Contact)	0	0	0	
UCS Premium <small>* Feature enhancement incl. all Standard features</small>	IM (1:N)	0	0	0
	IM Continuity b/w clients (1:1 & 1:N)	0	0	0
	MS Outlook sync (Schedule)	0	0	0
	Video conference (9 party)	-	0	0
	Collaboration	-	0	0
	MS Exchange (Schedule)	0	0	0
	AD sync	0	0	0
	SSO	0	0	0
Organization chart	0	0	0	

iPECS UCS Main Features


iPECS UCS provides UCS standard for SME and UCS premium for enterprise businesses. As all features are designed for a business size, customers can experience an efficient investment as their business grows.



Integrated Presence



Instant Message



Audio Call & Conference

Integrated Presence

- Instant decision on reachability by status color
- Save time and cost through real-time communications with people who are available for collaborations
- Integrated DND setting is available for both iPECS UCS client and desk phone at the same time

Single & Multi Log-in by user license

- Single log-in : Support log-in on to one client at a time (Basic/Advanced user license)
- Multi log-in : Support log-in on to multiple devices at the same time with single ID/PW (Power user license)

Audio Call & Conference

<Audio Call>

- Call popup : Display caller's information based on CID
- MS Outlook popup : Display caller's contact information in MS Outlook based on CID
- Call memo : Noting important information during a call
- Call recording : Easy on-demand call recording in local storage

<Audio conference>

- Easy conference building by graphical user interface and drag and drop
- Conference control features : Invite, Remove, Mute, Changing Master, Record

Video Call & Conference

- Build face to face conference at anytime, anywhere
- Maximum 9 party, 8 group video conference
- Video resolution : QCIF, CIF, VGA, 4CIF (704 x 480/576)
- Ad-hoc/Meet-me conference and e-mail notification
- Application sharing during conference /Remote monitoring, still shot

Supporting iOS CallKit – Mobile iOS Client

- Tight integration with the iOS UI using iOS CallKit
- Answering incoming UCS call on the lock screen
- Receiving mobile call during UCS call / Receiving UCS call during mobile call
- Making UCS call from the native phone app's contacts, favorites and recent

Call Control

- Call control on iPECS UCS desktop client for the desk phone calls
 - Most call control function can be executed by one click or drag and drop (Answer/Drop/Deny/Transfer/Hold/Park)
 - Flexible button sync between desk phone and UCS desktop client*
- * Support only in UCS desktop client

Instant Messaging, SMS and Note

- Easy user interface of IM; Inviting others simply by drag and drop
- IM continuity among clients
- Send and receive text messages to other internal iPECS system or external SMS users
- Leave a note for offline iPECS UCS user

Applications for Business Performance


Every business has different communications needs and meeting these needs is critical for designing business communications solution. iPECS UCP offers wide range of business applications for you to fulfill all the needs regardless your business size or industry.




iPECS Attendant Office



iPECS Attendant Hotel



iPECS IPCR



iPECS ClickCall

iPECS Attendant Office

IP based Attendant application for quick and easy call handling

- Easier management of call handling : Quick and easy call handling with simple clicking or drag and drop for an attendant
- Wait time and priority based call handling with caller information
- Phone and status presence based call routing
- Embedded IP softphone : Various call features of iPECS platform
- Desktop call control mode supported
- Directory service/phonebook management

iPECS Attendant Hotel

Hotel solution optimized for small to medium sized hotels

- Effective front desk and staff work
- Maximize guest service
- Effective Call Management
- Productivity features :
 - Various Hotel features
 - Various and quick alternative contacts
 - Flexible and configurable layout and user interface
 - Statistic report and Snapshot of group monitoring
 - Local language support

iPECS IPCR

Optimized and integrated IP Call Recording solution

- Simple and cost effective solution designed by a single vendor
 - Single IP connection for all call and all terminal recording
 - Cost effective single server call recording
 - Support server redundancy
- Powerful value added features
 - Voice packet encryption and call recording at the same time
 - Flexible deployment without limiting functionality
 - Agent monitoring
 - Remote maintenance and automatic alarming
- Intuitive user interface
 - Users can easily access the recording files over web browser
 - Intuitive graphical display
 - Powerful statistics features with real time graphic view and search options
 - User base access level management

iPECS ClickCall

Standard windows application for easy dialing

- Click to call from any selectable number in Windows application
 - Easy dialing of selectable number from Windows applications
 - Show dialed call log up to 10
 - Exit/Setup only through the icon in Windows tray
 - Setup dialing information
 - Multi language support
- Call control client without voice module
- Easy installation : Simple call client without dedicated server



iPECS CCX

iPECS CCX

Browser-based multi-channel IP Contact Center

- Contact Center solution integrated with iPECS platforms
 - Multi-channel inbound and outbound contact center
 - iPECS IPCR is provided for a call recording
- Benefits of all software solution
 - Software based media processing through SIP
 - No PSTN media interface card
 - Interactive Voice Response (IVR)
 - Monitoring and report
 - Agent's desktop software
- Next generation single multimedia solution
 - Email, Voice Mail, Fax, Web chat
 - Social networking with Facebook and SMS server
 - Multimedia outbound Tele-Marketing



iPECS CCX Report Plus

iPECS CCX Report Plus

Real-time monitoring and reporting for small sized Contact Centers

- Call distribution based on built-in ACD functionalities of call server
- Saving and displaying call accounting and ACD data generated from call server
- Real-time information display for supervisor and management
- Personal statistics for agent reporting and performance review
- Accesses anywhere - use dashboard in the company or remote office
- Simple for user to configure and create multiple dashboard screens



Terminals

iPECS UCP supports an extensive range of terminals from IP/Digital to IP DECT. These are designed for business users who require a wide range of feature-rich telephony devices to match your constantly changing business needs. iPECS UCP will give you an access to a large portfolio of terminals to optimize your unique business telephony needs.

IP Phones

1080i Premium

Premium Gigabit video IP Phone

- 7" (1024 x 600) touch & color display
- Up to 48 programmable keys with 12 self-label keys
- HD video with high resolution (HD720p) and 8M pixel camera
- HD audio for handset and speaker with wideband codec (G.722, Opus)
- Full duplex speakerphone with wideband voice
- Dual Gigabit Ethernet ports
- 2 USB ports for charging mobile devices and USB accessories
- Built-in Wi-Fi, Built-in Bluetooth and HDMI port supported
- OS Version: Android 10



1050i Advanced



Advanced Gigabit color IP Phone

- 8 line 4.3" (480 x 272) color display
- Up to 36 programmable keys with 12 self-label keys
- HD audio for handset and speaker with wideband codec (G.722, Opus)
- Full duplex speakerphone with wideband voice
- Dual Gigabit Ethernet ports
- 1 USB port for charging mobile devices and USB accessories

1040i Professional



Professional Gigabit color IP Phone

- 6 line 3.5" (480 x 320) color display
- Up to 24 programmable keys with 8 self-label keys
- HD audio for handset and speaker with wideband codec (G.722, Opus)
- Full duplex speakerphone with wideband voice
- Dual Gigabit Ethernet ports
- 1 USB port for charging mobile devices and USB accessories

1030i Essential



Essential Gigabit color IP Phone

- 6 line 2.8" (320 x 240) color display
- Up to 18 programmable keys with 6 self-label keys
- HD audio for handset and speaker with wideband codec (G.722, Opus)
- Full duplex speakerphone with wideband voice
- Dual Gigabit Ethernet ports

1020i

Basic



Basic Gigabit IP Phone

- 4 line 2.8" (132 x 64) grayscale display
- Up to 16 programmable keys with 4 self-label and 4 paper-label keys
- HD audio for handset and speaker with wideband codec (G.722, Opus)
- Full duplex speakerphone with wideband voice
- Dual Gigabit Ethernet ports

1010i

Entry



Cost effective entry IP Phone

- 4 line 2.4" (132 x 64) BW display
- 4 self-label programmable keys
- HD audio for handset and speaker with wideband codec (G.722, Opus)
- Full duplex speakerphone with wideband voice

Button Kit



1048ilss

- 48 buttons DSS (LCD type underlay)
- Compatible with 1020i, 1030i, 1040i, 1050i, 1080i



1024idss

- 24 buttons DSS (Paper type underlay)
- Compatible with 1020i, 1030i, 1040i, 1050i, 1080i



1048idss

- 48 buttons DSS (Paper type underlay)
- Compatible with 1020i, 1030i, 1040i, 1050i, 1080i

EHSA

Electronic Hook
Switch Adapter



Enable remote control for well-known EHS Headsets

- Compatible with 1020i, 1030i, 1040i, 1050i
- Wired and wireless EHS devices support
- Stable and better quality operation
- EHS headset support :
 - Plantronics (Savi 700 series, CS 500 series)
 - Jabra (PRO 920, 925, 9450, 9460, 9470, Duo 9460, 9465)
 - Sennheiser EHS (D10, DW Pro, SDW 5000)



Digital Phones



LDP-9240D

- 320 X 144 graphic LCD with backlit
- 12 Flexible buttons (Dual LED, 12 X 2)
- Full duplex speaker phone
- Support DSS button kit
- Support EHSA



LDP-9224DF

- 192 X 36 graphic LCD with backlit
- 24 Flexible buttons(Dual LED)
- Full duplex speaker phone
- Support DSS button kit
- Support EHSA




LDP-9224D

- 3 X 24 character LCD
- 24 Flexible buttons(Dual LED)
- Half duplex speaker phone
- Support DSS button kit
- Support EHSA



LDP-9208D

- 2 X 24 character LCD
- 8 Flexible buttons(Dual LED)
- Half duplex speaker phone
- No Support DSS Button Kit



LDP-9248DSS

- Support : LDP-9240D/24DF/24D
- Flexible button : 48 with 3 color LED
- Underlay type : Paper
- DSS connection : Up to 2



LIP-9024DSS

- Support : LDP-9240D/24DF
- Flexible button : 24 with 3 color LED
- Underlay type : Paper
- DSS connection : 1



LIP-9012DSS

- Support : LDP-9240D/24DF
- Flexible button : 12 with 3 color LED
- Underlay type : Paper
- DSS connection : 1



EHSA (Electronic Hook Switch Adaptor)

- Support : LDP-9240D/24DF/24D
- Wired and wireless EHS devices support
- Stable and better quality operation
- EHS headset support :
Plantronics (Savi 700 series, CS 500 series)
Jabra (PRO 920, 925, 9450, 9460, 9470, Duo 9460, 9465)
Sennheiser EHS (D10, DW Pro, SDW 5000)

IP DECT Phones



150dh

- 2 inch TFT Color LCD
- 200/17 hrs standby/talk time
- 250 local phonebook
- Emergency button
- IP65 compliant
- Pull cord support
- Man-down support
- bluetooth for headset
- 16 languages
- 3.5mm headset jack



GDC-800H

- 2 inch TFT Color LCD
- 200/18 hrs standby/talk time
- 100 local phonebook
- 16 languages
- Emergency button (ok button)
- 3.5mm headset jack



120dh

- 2 inch TFT Color LCD
- 350/22 hrs standby/talk time
- 100 local phonebook
- 16 languages



130db

- Max 254 base station in a zone
- Up to 1,000 handsets registerable
- 8/9 simultaneous calls (Mult-cell case/ Single cell case)
- Narrow or Wide Band audio
- Mutual Authentication
- Software Upgrade Over The Air
- Air sync and LAN sync
- Central Directory



110db


- Single base
- 1 repeater for coverage expansion
- Up to 20 users can be registered
- 5 simultaneous calls
- Narrow or Wide Band audio
- Central Directory



100dr

- Professional DECT repeater
- Number of repeaters with 110db/130db
110db: max 1 repeater
130db: 50 bases and 3 repeaters per base
127 bases and 1 repeater per base
254 bases and 0 repeater
- Range (open / Building) : up to 300m / 50m
Max coverage is dependent on environments.

iPECS UCP Network



System Capacity

Category		UCP100	UCP600	UCP2400	vUCP	Remark
Main cabinet			10 Slot		-	10 th slot is for PSU
System ports (Default)		199 (50)	600 (100)	2,400 (600)	2,400 (50)	
IP Extension (Default)		199 (30)	600 (10)	2,400 (10)	2,400 (30)	
CO/IP Line		199	600	998	-	
UCS Standard clients	Default Option 1 (Desktop/Mobile)	2/2	10/10	20/20	-	Only one default option can be used
	Default Option 2 (Advanced User)	2	10	20	2	
	Max	100	200	400	400	
UCS Premium clients		199	600	2,400	2,400	
Clickcall (Default)		199 (2)	600 (10)	2,400 (10)	2,400 (2)	
Server Redundancy	Local/Geographical	-	O / O	O / O	- / O	w/ License for Geographical
Integrated Telephony ports	Standard/option	2FXS/option	-	-	-	4CO or 2BRI or 4BRI
	Built-in VOIP DSP*	2~6	6	-	-	Default
VoIP Channel	Built-in VOIP Switching**	16	24	-	Max. 126ch (default 6ch)	Built-in vVOIM
					Max. 246ch	External vVOIM
	System Max	199	600	998	998	
Built-in Audio Conference***		6/10/14/18	6/18	-	-	
VM	Built-in VM (Default)	8 ch/14 hrs (8/4)	8 ch/16 hrs (8/6)	-	Max. 64ch (8)	Built-in vUVM
	External VM (Default)		16 ch/200 hrs (8/50)		Max. 144ch/500hrs	External vUVM
UVM/vUVM per system			30/1		30/1	
MCIM/vMCIM**** per system			30/30		30/30	
Attendant			50		50	
Serial Port (RS-232C) / USB (3.0) Host Port			1/1		-	

* In-band/Out-band SIP, Transcoding, Networking, Remote IP Phone/Devices

** Out-band SIP, Networking, Remote IP Phone/Devices

*** VoIP DSP channels can be assigned to the MCIU, 2 VoIP = 4 Conf channels **** MCIM supports 4-32 party conferencing

Power Requirement

Item	Description	Specification
Module AC/DC Adapter	AC Voltage Input	100~240VAC +/- 10% @ 50/60Hz
	AC Current Input	1.0 amps
	DC Output	48 VDC @ 0.8 amps
Keypad AC/DC Adapter	AC Voltage Input	100~240VAC +/- 10% @ 50/60Hz
	AC Current Input	0.2 amps
	DC Output	48 VDC @ 0.3 amps
PSU	AC Voltage Input	100~240VAC +/- 10% @ 50/60Hz
	Fuse	T6.3, AC250V
	DC Output	48 VDC, 5.3 amps/5VDC @ 1 amps

Dimension & Weight

WxHxD (mm)	Standard Gateway Module	38.8 x 230 x 194.5
	Main Cabinet, Enhanced	440 x 265.6 x 318.2
	19" Rack Mount modules	436.6 x 53 x 318
Weight (Kg)	Standard Gateway Module	1.5
	Main Cabinet, Enhanced (with PSU module)	7.78(9.32)
	19" Rack Mount modules	4.32

Operating Environment

Temperature	0(°C) - 40(°C)/32(°F) - 104(°F)
Humidity	0 - 80%(Non-condensing)

System Components

Item	Board	Description
UCP Call Server	UCP100	Unified Communications Platform Server 100, Basic 50, Up to 199 port
	UCP600	Unified Communications Platform Server 600, Basic 100, Up to 600 port
	UCP2400	Unified Communications Platform Server 2400, Basic 600, Up to 2,400 port
	vUCP	Virtual Unified Communications Platform, Basic 50, Up to 2,400 port
Trunk Gateway	VCIM*	VOIP/Audio conference Module (Default 64 DSP channel, upto 128 channel)
	VOIM8/24	8/24 ch VoIP Interface Module
	LGCM4/8	4/8 port Analog CO Interface Module
	BRIM2/4	2/4 BRI(4/8 ch) Interface Module
	PRIM	1 port PRI(30 ch) Interface Module
	vVOIM	250ch Virtual VoIP Interface Module (G.711 only)
	vVOIMT	32 ch Virtual VoIP Interface Module for Transcoding
Extension Gateway	DTIM8/24	8/24 port Digital Line Telephone Interface Module
	SLTM4/8/32	4/8/32 port Single Line Telephone Interface Module
Other Gateway	MCIM	32 ch Multi-media conference interface module
	vMCIM	64 ch Virtual Multi-media conference interface module
	UVM	16 ch / 200 hrs Unified Voice Mail Module
	vUVM	Virtual Unified Voice Mail Module (150 ch / 500 hrs)
	ES8G/ES8GP	8 ports Gigabit switch/ 8 ports Gigabit PoE switch

* VoIP and Audio Conference can be mixed use. 1 VoIP channel uses 2 DSP channels and 1 Audio Conference channel uses 1 DSP channel

iPECS vUCP Server Requirement

VMware

- VMware vSphere ESXi 6.0 or above

Hardware server requirement

- CPU: Intel Xeon family with 2.0GHz clock speed or higher
- Memory*: 12G Bytes or higher
- Network: 1 Ethernet interface
- HDD*: 100G Bytes or higher

* Must satisfy the ESXi requirements in addition to the specific RAM and HDD requirements of each deployed virtual machine

Category	vUCP	vUVM	vVOIM	vVOIMT	vMCIM
CPU	1 vCore	1 vCore	1 vCore	1 vCore	1 vCore
Memory	4G Bytes	4G Bytes	4G Bytes	1G Bytes	1G Bytes
HDD	24G Bytes(App) 1G Bytes(DB data)	24G Bytes(App) 16G Bytes(Voice files)	24G Bytes(App)	8G Bytes(App)	8G Bytes(App)
Network	1 Gigabit	1 Gigabit	1 Gigabit	1 Gigabit	1 Gigabit

AWS

Profile of Virtual Machine

Category	vUCP	vUVM	vVOIM	vVOIMT	vMCIM
Instance type	t2.micro	t2.micro	t2.micro	t2.micro	t2.micro
HDD	8G Bytes(App) 1G Bytes(DB data)	8G Bytes(App) 16G Bytes(Voice data)	8G Bytes(App)	8G Bytes(App)	8G Bytes(App)
Network	1 Ethernet, DHCP	1 Ethernet, DHCP	1 Ethernet, DHCP	1 Ethernet, DHCP	1 Ethernet, DHCP

Microsoft Azure

Profile of Virtual Machine

Category	vUCP	vUVM	vVOIM	vVOIMT	vMCIM
VM size	Standard B1s	Standard B1s	Standard B1s	Standard B1s	Standard B1s
HDD	8G Bytes(App) 1G Bytes(DB data)	8G Bytes(App) 16G Bytes(Voice data)	8G Bytes(App)	8G Bytes(App)	8G Bytes(App)
Network	1 Ethernet, DHCP	1 Ethernet, DHCP	1 Ethernet, DHCP	1 Ethernet, DHCP	1 Ethernet, DHCP

#. Please refer to the installation manual for detailed specifications.

